



www.vinylchem.com

Vinyl Chemicals Private Limited

Sales Office

15-7-406, 1st Floor, Begum Bazar, Hyderabad – 500012 INDIA

TEL: 91-40-24743825 FAX: 91-40-24605057

India Sales: sales@vinylchem.com

Export: export@vinylchem.com

PRODUCT DATA

CALCIUM STEARATE {CS}

CAS. NO: 1592-23-0

SPECIFICATION	DETAIL
CHEMICAL FORMULA	Ca (C17 H35 COO) 2
SPECIFICATIONS	Appearance : Fine Creamish White Powder Specific Gravity : 1.0 - 1.1 Ash Content : 9.5 % - 10.5 % Melting Point: : 115 C +- 5 C Fineness : 99 % Min. (Through B.S. 240 mesh) Moisture % : 2 % Max. Bulk Density : 0.2 – 0.25 gm/cc
PROPERTIES AND APPLICATIONS	This is an excellent high melting internal lubricant widely used in rigid processing. This is also used for making nontoxic compounds along with Zinc Stearate and Epoxy oil. This is also used in Cosmetics and as mould releasing agent for various polymers.
RECOMMENDED DOSAGE	Up to 1.5 PHR
PRODUCT PACKAGING	25 Kg. HDPE Laminated Woven Sacks with inside Polythene Liners