



www.vinylchem.com

Vinyl Chemicals Private Limited

Sales Office

15-7-406, 1st Floor, Begum Bazar, Hyderabad – 500012 INDIA

TEL: 91-40-24743825 FAX: 91-40-24605057

India Sales: sales@vinylchem.com

Export: export@vinylchem.com

PRODUCT DATA

LEAD STEARATE {LS}

CAS. NO: 1072-35-1

SPECIFICATION	DETAIL
CHEMICAL FORMULA	Pb (C17 H35 COO) 2
SPECIFICATIONS	Appearance : Fine Creamish White Powder Specific Gravity : 1.3 - 1.4 Lead Content as PbO : 29 – 31% Melting Point: : 110 C – 115 C Fineness : 99 % Min. (Through B.S. 240 mesh) Moisture % : 0.1 % Max. F.F.A : 0.5 % Max
PROPERTIES AND APPLICATIONS	This is a moderate heat stabilizer and is one of the best lubricants for PVC. It functions both as internal & external lubricant. It shows better heat stability when used in combination with other metallic stearate like Barium & Cadmium Stearate. It shows better heat stability in processing flexible compounds at low temperatures and high-speed extrusions.
RECOMMENDED DOSAGE	Up to 1.0 PHR
PRODUCT PACKAGING	25 Kg. HDPE Laminated Woven Sacks with inside Polythene Liners