



www.vinylchem.com

Vinyl Chemicals Private Limited

Sales Office

15-7-406, 1st Floor, Begum Bazar, Hyderabad – 500012 INDIA

TEL: 91-40-24743825 FAX: 91-40-24605057

India Sales: sales@vinylchem.com

Export: export@vinylchem.com

PRODUCT DATA

ZINC STEARATE {ZS}

CAS. NO: 557-05-1

SPECIFICATION	DETAIL
CHEMICAL FORMULA	Zn (C17 H35 COO) 2
SPECIFICATIONS	Appearance : Fine White Powder Bulk Density : 0.10 – 0.2 gms/cc Residue on BS 240 Mesh : None Moisture % : 1 % Max. Ash Content % : 13.5 – 15.5 % Free Fatty Acids : 1 % Max Soluble Chloride & Sulphate : 1 % Max Iron Contents : Less than 40 ppm
PROPERTIES AND APPLICATIONS	Zinc Stearate is used in Rubber industry mainly as mould release agent. It finds application in Cosmetics, pharmaceuticals, paints, plastics and many other industries. In PVC industry Zinc Stearate is normally used with calcium Stearate as non-toxic, non-sulphur staining stabilizer. It is also used as lubricant in manufacture of coloured Master batches.
PRODUCT PACKAGING	25 Kg. HDPE Laminated Woven Sacks with inside Polythene Liners